



LUMINOUS LED - 300mm OVERHEAD RAIN SHOWER (ROUND)

WATER EFFICIENT TAPWARE

PLUMBERS INSTALLATION INSTRUCTIONS

Important Information

- * Available as shower head only, wall and ceiling mounted shower arms are sold separately.
- * Shower head is fitted with a flow regulator.
- * Not suitable for gravity feed systems.
- * All pipework must be thoroughly flushed prior to installation, as foreign materials may block the flow regulating device and reduce the flow of water.

Installation

- 1) Check that threaded nipple (2) is the correct length, as shown. Cut to length if required ensuring end face is square. Apply thread tape to the thread.
Important : Care must be taken that thread tape cannot become dislodged and block the flow regulating device, causing a reduction in water flow.
- 2) Place the cover plate (1⁺) over the threaded nipple (2). Screw the shower arm (3⁺) onto the threaded nipple (2) and position as required. DO NOT OVERTIGHTEN.
- 3) Ensure strainer washer (5) is fitted to the inlet socket of the showerhead (6), then screw the showerhead (6) onto the outlet thread of the shower arm (3⁺). Tighten using a suitable spanner, taking care not to damage the decorative finish.

IMPORTANT

Pressure & Temperature Requirements.

- Hot and cold water inlet pressures should be equal.
- Static inlet pressure range : 150 -1000 kPa
New Regulation:- 500 kPa maximum static pressure at any outlet within a building. (Ref. AS/NZS 3500.1)
- Maximum hot water temperature : 80°C.

