

# Contura

Vitreous China 4.5/3 litre Dual Flush  
Wall Faced Close-Coupled Toilet Suite



# Contura



With a curvaceous and organic design to elevate your bathroom surroundings, the **Contura** wall faced close coupled toilet suite brings soul to your functional bathroom products. The pan connection system includes the patented Caroma Uni-Orbital® connector for increased installation flexibility. The Caroma Uni-Orbital® connector extends to any position up to a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 225mm with a recommended setout of 140mm. The suite is suitable for commercial projects and domestic applications. Fitted with chrome plated push buttons, the smooth sided pan design with a contoured seat offer a seamless integration for simple luxury.

- Pan:** **Contura** 4.5 litre full flush washdown pan with a fully glazed rim and trap.
- Traps:** Universal trap for S or P-trap installations.
- Cistern:** **Contura** cistern shroud conceals an integrated dual flush cistern and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back entry only.  
Cistern inlet stop valve and inlet flex tube connection is concealed within the cistern shroud and is included.  
**Vandal Resistant System** – A vandal resistant system is incorporated to lock the shroud onto the cistern tank.  
**Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**
- Fixing:** The cistern tank is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.
- Seats:** The **Contura** soft close toilet seat is provided as standard with the Contura suite. A quality solid section compression moulded toilet seat, fitted with buffers and metal hinges.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

**Uni-Orbital® Connector**  
Setout Range 60mm to 225mm  
(up to 50mm sideways adjustment)

Pan foot level  
140 recommended (range 60 – 225mm with Uni-Orbital® connector supplied - up to 50mm sideways adjustment)

**Contura Wall Faced Close Coupled Toilet Suite with Contura Soft Close Seat**

Code No.
4.5/3 litre Back Entry
Internal Overflow
839400

Setout position for 1/2" B.S.P. Nipple

Centre water back inlet connection

**Important**  
22mm approx. projection from wall  
1/2" B.S.P. Nipple  
Finished wall

**D82 Concealed Fixing Bracket**

**Note:** All height dimensions to underside of pan, make allowance for bedding when installing.  
**Bedding:** The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.  
**Bracket fixing:** The pan should be bedded with an acetic cured silicone sealant and fixed with the D82 Fixing Brackets supplied.