



HYDROTAP G5 BA CUBE GUNMETAL



BOILING



AMBIENT

FILTERED

Order Code H53785Z09AU

Zip HydroTap Design Range Boiling, Ambient, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.



Manufacturing Code	H53785Z09AU
--------------------	-------------

Capacity	Residential
----------	-------------

Tap	Zip HydroTap Design Range CUBE Tap (Gunmetal)
Water Pressure	Min 170kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.35kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

8/13/2021

HydroTap G5 BA Cube Gunmetal | Zip Water

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

HydroTap Tap options

HydroTap Arc Tap

20

162

40

175-225

83

115

194

303-353

20

162

40

175-225

83

115

194

276-326

HydroTap Cube Tap

20

162

40

175-225

83

115

194

276-326

Standalone Font with Arc Tap

162

225

223

174

40

140

176

353

Cutting detail

174

3-off, 10 holes @ 155mm PCD, equispaced

140

hole for bowl

176

outline of Font

35

hole for tap

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

200

333

50

50

Command Centre width

Air outlet louvre (if required)

Cut-out in door/wall, towards the top of the cabinet

285

60

Air inlet cut-out (required)

Cut-out in cabinet floor

max. 43

326

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

35mm hole for HydroTap Tap

HydroTap Arc

Clearance Envelope

200 min.

333

50 min.

280

50 min.

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

4mm buffer pad air space

Clearance Envelope

313

HydroTap G5

B Home, B60, B100

BA Home, BA60, BA100

shown with HydroTap Arc

<https://www.zipwater.com/shop/hydrotap/zip-hydrotap-cube-ba-100-H53785Z00AU/zip-hydrotap-cube-ba-100-H53785Z09AU>

2/3

